

job name:
 type:

Quick Ship imago™ LED spec sheet

Quick Ship

Need fixtures quick? Get up to 10 pieces of our imago™ LED series in 10 business days or less. Need more than 10, contact your local Rep for our current lead times. Orders are Ground Freight Allowed.

driver housing

extruded aluminum heat sink with silver anodized finish.

diffuser

.25" parabolic matte white acrylic.

modular construction

modular fixture design allows for LED driver and COB array to be replaced in the field.

LED

COB array in 3500K (80 cri). under normal operating conditions, the LEDs employed are rated for >55,000hrs L70 (6.8K) per IES TM-21 from LM-80 test data, and 200,000hrs L70 projected life. white power cord is standard.

driver

integral, class P programmable, class A sound rating, universal input (120-277 vac), 1% minimum dimming level, PF >90, THD <20% at full load, open/short circuit protection. input/output isolation, surge protection (3KV), wired for 0-10v dimming from factory.

mounting

5"dia. spun steel canopy in satin white with single 6ft stainless steel cables and field adjustable grippers that allow for exact AFF mounting heights.

emergency

if required, recommend use of inverter (by other).



catalog number

QSP3512	35K	AN
size	LED array	powerhead finish
QSP3512 12"dia X 21"ht	35K 3500K	AN silver anodized

Cat No	Delivered Lumens	Watts		Amps	
		120V	277V	120V	277V
QSP3512		35	35	.29	.13
3500K	3080				

