

job name:
 type:

Quick Ship tiki™ LED spec sheet

Quick Ship

Need fixtures quick? Get up to 10 pieces of our bul.it™ LED series in 10 business days or less. Need more than 10, contact your local Rep for our current lead times. Orders are Ground Freight Allowed.

material

housing
 two-piece precision CNC spun .063" aluminum. downlight housing with rolled bottom edge for added strength. inverted bell uplight element.

downlight array platform
 .080" spun aluminum.

optics

.050" spun aluminum conical reflector finished in high reflectance (>92%) matte white powder coat.

LED

COB array in 3500K (80 cri). under normal operating conditions, the LEDs employed are rated for >55,000hrs L70 (6.8K) per IES TM-21 from LM-80 test data, and 200,000hrs L70 projected life. Dual Distribution Direct/Indirect, & single driver both direct and indirect LEDs. white power cord is standard.

driver

integral, class P programmable, class A sound rating, universal input (120-277 vac), 1% minimum dimming level, PF >90, THD <20% at full load, open/short circuit protection. input/output isolation, surge protection (3KV), wired for 0-10v dimming from factory. Dual Distribution Direct/Indirect.

mounting

5"dia. spun steel canopy in satin white with 6ft stainless steel cable tripod and field adjustable grippers that allow for exact AFF mounting heights.

finish

silver anodized finish.

emergency

if required, recommend use of inverter (by other).



catalog number

QSP5113	35K	AN
size QSP5113 13"dia X 16"ht	LED array 35K 3500K	powerhead finish AN silver anodized

Cat No	Direct Delivered Lumens	Watts		Amps		Indirect Delivered Lumens*	Watts		Amps	
		120V/277V	120V	277V	120V/277V		120V	277V		
QSP5113 HI		46	.38	.17		29	.24	.10		
3500K	3127				1952					

