

job name:   
 type:

## 9" top.is.tiki™ spec sheet

### material

#### housing

precision CNC spun .063" aluminum. tapered drum with rolled bottom edge for added strength.

#### array platform

.080" spun aluminum.

#### bottom lens (optional)

.125" P95 frosted acrylic flat lens with 3 finger holes.

#### decorative ring (optional)

.125" colored acrylic ring.

### optics

.050" spun aluminum conical reflector finished in high reflectance (>92%) matte white powder coat.

### LED module

COB array in 2700K, 3000K, 3500K, or 4000K. (call factory for 5000K) (80+ cri standard) optional 90cri (see below). under normal operating conditions, the LEDs employed are rated for >50,000hrs L70 (6.8K) per IES TM-21 from LM-80 test data.

### driver

integral, class 2, universal input (120-277v), constant current, 0-10v dimming, 1% minimum dimming level, PF >.9, THD <20%, protections include open and short circuit, overload and over temperature.

### mounting

5"dia. spun steel canopy in satin white with 6 ft stainless steel cable tripod and field adjustable grippers that allow for exact AFF mounting heights. or select 12ft adjustable suspension. (drawing below)

### premium mountings

#### colored cloth cord (optional)

spun aluminum canopy painted to match fixture. ultrathin vertical stainless steel cable and field adjustable gripper that allow for exact AFF mounting heights. cloth-covered power cord color options listed below. cord requires special stripping tool (link).

#### power over cable (optional)

spun aluminum canopy painted to match fixture. Class 2 LED powered suspension system that suspends and powers the fixture with thin stainless steel copper-core conductive cables, providing a clean look without the need for a separate power cord. powered suspension requires cable cutter (link) specifically designed to cut stainless steel aircraft cable from 1/32" to 1/8".

### finish

select from standard powder coat paint finishes or specify RAL# for custom colors.

### emergency

recommend use of inverter (by other).


optional WREM: wired for remote EM battery (by other). if using WHPC, SBPC, or BKPC cords, 2nd power cord required.



## catalog number


P4909					
-------	--	--	--	--	--

size	CCT	lumens	painting finishes	power cord	options
<b>P4909</b> 9"dia X 8.5"ht  see pages 2 & 3 for info on P4913 and P4917	<b>27</b> 2700K  <b>30</b> 3000K  <b>35</b> 3500K  <b>40</b> 4000K	<b>LO</b> 1125 lm  <b>HI</b> 2250 lm  <b>HX</b> 3155 lm	<b>AP</b> anodized paint <b>BN</b> brown <b>BR</b> brick red <b>BS</b> brass <b>BU</b> blue <b>BZ</b> bronze <b>CP</b> champagne <b>FB</b> flat black <b>GM</b> gun metal <b>GR</b> green <b>MB</b> military blue <b>MN</b> mint <b>MW</b> matte white <b>OR</b> orange <b>PL</b> purple <b>RD</b> red <b>SB</b> satin black <b>SS</b> satin silver <b>TG</b> textured gray <b>TW</b> textured white <b>YO</b> yellow	<b>WHPC</b> white power cord and canopy <b>BKPC</b> black power cord and canopy <b>SBPC</b> silver braid power cord and white canopy  <b>premium</b> (driver canopy required) (not available w/ 12ft option) <b>BUPC</b> blue cloth cord <b>ORPC</b> orange cloth cord <b>PLPC</b> purple cloth cord <b>RDPC</b> red cloth cord <b>WGPC</b> white & gray dot cloth cord <b>POC</b> power over cable	<b>6FT</b> 72" cables <b>12FT</b> 12ft adjustable suspension* <b>90CRI</b> <b>BL</b> Bottom lens <b>DRA</b> amber decorative ring <b>DRB</b> blue decorative ring <b>DRF</b> frost decorative ring <b>DRG</b> green decorative ring <b>DRR</b> red decorative ring <b>DRY</b> yellow decorative ring <b>WREM</b> wired for remote EM battery pack (by other) (see note above)  *not available with premium power cords



### premium finish

**RAL** specify RAL#



job name:   
 type:

# 13" top.Is.tiki™ spec sheet

**material**

**housing**

precision CNC spun .063" aluminum. tapered drum with rolled bottom edge for added strength.

**array platform**

.080" spun aluminum.

**bottom lens** (optional)

.125" P95 frosted acrylic flat lens with 3 finger holes.

**decorative ring** (optional)

.125" colored acrylic ring.

**optics**

.050" spun aluminum conical reflector finished in high reflectance (>92%) matte white powder coat.

**LED module**

COB array in 2700K, 3000K, 3500K, or 4000K. (call factory for 5000K) (80+ cri standard) optional 90cri (see below). under normal operating conditions, the LEDs employed are rated for >50,000hrs L70 (6.8K) per IES TM-21 from LM-80 test data.

**driver**

integral, programmable, class 2, universal input (120-277v), constant current, 0-10v dimming, 1% minimum dimming level, PF >.9, THD <20%, protections include open and short circuit, overload and over temperature.

**mounting**

5"dia. spun steel canopy in satin white with 6ft stainless steel cable tripod and field adjustable grippers that allow for exact AFF mounting heights. or select 12ft adjustable suspension. (drawing below)

**premium mountings**

**colored cloth cord** (optional)

spun aluminum canopy painted to match fixture. ultrathin vertical stainless steel cable and field adjustable gripper that allow for exact AFF mounting heights. cloth-covered power cord color options listed below. cord requires special stripping tool (link).

**power over cable** (optional)

spun aluminum canopy painted to match fixture. Class 2 LED powered suspension system that suspends and powers the fixture with thin stainless steel copper-core conductive cables, providing a clean look without the need for a separate power cord. powered suspension requires cable cutter (link) specifically designed to cut stainless steel aircraft cable from 1/32" to 1/8".

**finish**

select from standard powder coat paint finishes or specify RAL# for custom colors.

**emergency**

recommend use of inverter (by other).



optional WREM: wired for remote EM battery (by other). if using WHPC, SBPC, or BKPC cords, 2nd power cord required.



## catalog number

P4913					
-------	--	--	--	--	--

size	CCT	lumens	painted finishes	power cord	options
<b>P4913</b> 13"dia X 12"ht  see page 3 for info on P4917	<b>27</b> 2700K  <b>30</b> 3000K  <b>35</b> 3500K  <b>40</b> 4000K	<b>FX</b> 1600 lm  <b>LO</b> 2900 lm  <b>HI</b> 3700 lm  <b>HX</b> 5000 lm  <b>CL*</b> xxxx lm custom lumens consult factory	<b>AP</b> anodized paint <b>BN</b> brown <b>BR</b> brick red <b>BS</b> brass <b>BU</b> blue <b>BZ</b> bronze <b>CP</b> champagne <b>FB</b> flat black <b>GM</b> gun metal <b>GR</b> green <b>MB</b> military blue <b>MN</b> mint <b>MW</b> matte white <b>OR</b> orange <b>PL</b> purple <b>RD</b> red <b>SB</b> satin black <b>SS</b> satin silver <b>TG</b> textured gray <b>TW</b> textured white <b>YO</b> yellow	<b>WHPC</b> white power cord and canopy  <b>BKPC</b> black power cord and canopy  <b>SBPC</b> silver braid power cord and white canopy  <b>premium</b> (driver canopy required) (not available w/ 12ft option) <b>BUPC</b> blue cloth cord <b>ORPC</b> orange cloth cord <b>PLPC</b> purple cloth cord <b>RDPC</b> red cloth cord <b>WGPC</b> white & gray dot cloth cord <b>POC</b> power over cable	<b>6FT</b> 72" cables  <b>12FT</b> 12ft adjustable suspension*  <b>90CRI</b> <b>BL</b> Bottom lens <b>DRA</b> amber decorative ring <b>DRB</b> blue decorative ring <b>DRF</b> frost decorative ring <b>DRG</b> green decorative ring <b>DRR</b> red decorative ring <b>DRY</b> yellow decorative ring <b>WREM</b> wired for remote EM battery pack (by other) (see note above) *not available with premium power cords



**premium finish**  
RAL specify RAL#

job name:   
 type:

# 17" top.ls.tiki™ spec sheet

**material**

**housing**

precision CNC spun .063" aluminum. tapered drum with rolled bottom edge for added strength.

**array platform**

.080" spun aluminum.

**bottom lens** (optional)

.125" P95 frosted acrylic flat lens with 3 finger holes.

**decorative ring** (optional)

.125" colored acrylic ring.

**optics**

.050" spun aluminum conical reflector finished in high reflectance (>92%) matte white powder coat.

**LED module**

COB array in 2700K, 3000K, 3500K, or 4000K. (call factory for 5000K) (80+ cri standard) optional 90cri (see below). under normal operating conditions, the LEDs employed are rated for >50,000hrs L70 (6.8K) per IES TM-21 from LM-80 test data.

**driver**

integral, class 2, universal input (120-277v), constant current, 0-10v dimming, 1% minimum dimming level, PF >.9, THD <20%, protections include open and short circuit, overload and over temperature.

**mounting**

5"dia. spun steel canopy in satin white with 6ft stainless steel cable tripod and field adjustable grippers that allow for exact AFF mounting heights. or select 12ft adjustable suspension. (drawing below)

**premium mountings**

**colored cloth cord** (optional)

spun aluminum canopy painted to match fixture. ultrathin vertical stainless steel cable and field adjustable gripper that allow for exact AFF mounting heights. cloth-covered power cord color options listed below. cord requires special stripping tool (link).

**power over cable** (optional)

spun aluminum canopy painted to match fixture. Class 2 LED powered suspension system that suspends and powers the fixture with thin stainless steel copper-core conductive cables, providing a clean look without the need for a separate power cord. powered suspension requires cable cutter (link) specifically designed to cut stainless steel aircraft cable from 1/32" to 1/8".

**finish**

select from standard powder coat paint finishes or specify RAL# for custom colors.

**emergency**

recommend use of inverter (by other).


optional WREM: wired for remote EM battery (by other). if using WHPC, SBPC, or BKPC cords, 2nd power cord required.




## catalog number

P4917					
-------	--	--	--	--	--

size	CCT	lumens	painted finishes	power cord	options
<b>P4917</b> 17"dia X 15.75"ht	<b>27</b> 2700K	<b>FX</b> 2500 lm	<b>AP</b> anodized paint	<b>WHPC</b> white power cord and canopy	<b>6FT</b> 72" cables
	<b>30</b> 3000K	<b>LO</b> 3500 lm	<b>BN</b> brown	<b>BKPC</b> black power cord and canopy	<b>12FT</b> 12ft adjustable suspension*
	<b>35</b> 3500K	<b>HI</b> 5000 lm	<b>BR</b> brick red	<b>SBPC</b> silver braid power cord and white canopy	<b>90CRI</b>
	<b>40</b> 4000K	<b>HX</b> 6000 lm	<b>BS</b> brass	<b>premium</b> (driver canopy required) (not available w/ 12ft option)	<b>BL</b> Bottom lens
		<b>CL*</b> xxxx lm custom lumens consult factory	<b>BU</b> blue	<b>BUPC</b> blue cloth cord	<b>DRA</b> amber decorative ring
			<b>BZ</b> bronze	<b>ORPC</b> orange cloth cord	<b>DRB</b> blue decorative ring
			<b>CP</b> champagne	<b>PLPC</b> purple cloth cord	<b>DRF</b> frost decorative ring
			<b>FB</b> flat black	<b>RDPC</b> red cloth cord	<b>DRG</b> green decorative ring
			<b>GM</b> gun metal	<b>WGPC</b> white & gray dot cloth cord	<b>DRR</b> red decorative ring
			<b>GR</b> green	<b>POC</b> power over cable	<b>DRY</b> yellow decorative ring
			<b>MB</b> military blue		<b>WREM</b> wired for remote EM battery pack (by other) (see note above)
			<b>MN</b> mint		*not available with premium power cords
			<b>MW</b> matte white		
			<b>OR</b> orange		
			<b>PL</b> purple		
			<b>RD</b> red		
			<b>SB</b> satin black		
			<b>SS</b> satin silver		
			<b>TG</b> textured gray		
			<b>TW</b> textured white		
			<b>YO</b> yellow		




**premium finish**  
**RAL** specify RAL#





## Powder Coat Paint Finishes



**MW** matte white



**CP** champagne



**YO** yellow 1018



**TW** textured white



**BZ** bronze



**RD** red 3020



**AP** anodized paint



**BS** brass



**BU** blue 5017




**SS** satin silver



**GM** gun metal



**OR** orange 2011



**TG** textured gray



**BR** brick red



**MN** mint 6019




**FB** flat black



**BN** brown 8023



**GR** green 6018



**SB** satin black



**MB** military blue



**PL** purple 4005

For accurate color verification, actual finish samples are available upon request.

## Premium Finishes\*



**RAL#**

\*Available on select series. Consult product submittal for availability.

