

3.5"/6" sq.3™ spec sheet 90CRI

housing
3.5" smooth square extruded architectural 6063 aluminum outer housing in five lengths available in 15 standard powder coat paint finishes listed below. premium RAL and wood finishes also available. satin black canopy and cord standard on wood finishes.

LED
COB in 2700K, 3000K, 3500K, or 4000K (90 cri standard) rated >36,000 hours L70 (6.8K) per LM-80 test data, and 71,000 hours projected life per IES TM-21.

downlight optics
LEDiL® Angelina 82mm dia 31mm high (RoHS compliant) available in 20° spot, 30° medium, 50° wide with specular anodized finish. 90° extra wide features matte white highly reflective finish. color mixing sublens standard. standard mounting clamp allows for easy replacement of reflector in field. the typical total beam angle is the full angle measured where the luminous intensity is half of the peak volume.

driver
constant current, class P, class 2 power unit, class A sound rating, universal input (120-277V) programmable driver, 5% minimum dimming level, PF >0.90. protections include short circuit, input/output isolation and surge protection (3KV). wired for 0-10v dimming from factory.

mounting standard
driver in junction box (requires 2 1/8" deep electrical box). ultrathin vertical stainless steel cables and field adjustable grippers that allow for exact AFF mounting heights. cloth-covered power cord color options listed below. cloth cord requires special stripping tool (link). special universal mounting bracket allows EC to clock fixture orientation during installation. 5" sq. canopy painted to match fixture. satin black canopy and cord standard on wood finishes.

canopy mounted driver (CDVR) (optional)
5" sq. canopy with 3.5" x 3.5" extruded square, painted to match fixture (see image below). satin black canopy standard on wood finishes.

remote enclosure (.LV) (optional)
the standard driver can be remote mounted up to 33ft from the LED. suspension length should be considered in distance. remote enclosure supplied. for distances greater than 33ft consult factory. for Chicago Plenum installation consult factory.

power over cable (POC) (optional)
Class 2 LED powered suspension system that suspends and powers the fixture with thin stainless steel copper-core conductive cables, providing a clean look without the need for a separate power cord. powered suspension requires cable cutter (link) specifically designed to cut stainless steel aircraft cable from 1/32" to 1/8". 5"sq canopy painted to match fixture. satin black canopy standard on wood finishes.

finish
select from 15 standard powder coat paint finishes or 3 wood finishes (listed below) or specify RAL# for custom colors. satin black canopy and cord standard on wood finishes.


emergency
if required, recommend use of inverter (by other).

catalog number


--	--	--	--	--	--	--

size	beam	CCT	lumens	paint finish	power cord	options
P6603 driver in j-box	S 20° spot	27 2700K	L1 410 lm		BUPC blue cloth cord	3FT 36" cable(s)
P6603.LV remote enclosure	M 30° med	30 3000K	L2 715 lm	AP anodized paint	ORPC orange cloth cord	6FT 72" cable(s)
3.5"dia X 3.5 "ht	W 50° wide	35 3500K	L3 1025 lm	BS brass	PLPC purple cloth cord	CDVR canopy mounted driver
	XW 90° extra wide	40 4000K	H1 1435 lm	BU blue	RDPC red cloth cord	
				BZ bronze	WGPC white & gray dot cloth cord	
				CP champagne		
				FB flat black	POC power over cable	
				GM gun metal		
				MB military blue	WHPC white cord	
				MW matte white	BKPC black cord	
				OR orange	SBPC silver braid cord	
				RD red		
				SB satin black		
				SS satin silver		
				TG textured gray		
				YO yellow		

P6606 driver in j-box	S 20° spot	27 2700K	L1 410 lm	RAL specify RAL#		
P6606.LV remote enclosure	M 30° med	30 3000K	L2 715 lm	wood finish		
3.5"dia X 6 "ht	W 50° wide	35 3500K	L3 1025 lm	ASH ashwood		
	XW 90° extra wide	40 4000K	H1 1435 lm	ENG english brown oak		
			H2 2050 lm	ESP espresso		
			H3 2870 lm	satin black canopy and cord standard on wood finishes		



only specific sizes



This product meets the guidelines for the Build America, Buy America Act. Some Exclusions Apply. For more information and full list of eligible SKUs, please contact the factory at info@impactltg.com

12"/18"/24" sq.3™ spec sheet 90CRI

housing
3.5" smooth square extruded architectural 6063 aluminum outer housing in five lengths available in 15 standard powder coat paint finishes listed below. premium RAL and wood finishes also available. satin black canopy and cord standard on wood finishes.

LED
COB in 2700K, 3000K, 3500K, or 4000K (90 cri standard) rated >36,000 hours L70 (6.8K) per LM-80 test data, and 71,000 hours projected life per IES TM-21.

downlight optics
LEDiL® Angelina 82mm dia 31mm high (RoHS compliant) available in 20° spot, 30° medium, 50° wide with specular anodized finish. 90° extra wide features matte white highly reflective finish. color mixing sublens standard. standard mounting clamp allows for easy replacement of reflector in field. the typical total beam angle is the full angle measured where the luminous intensity is half of the peak volume.

driver
constant current, class P, class 2 power unit, class A sound rating, universal input (120-277V) programmable driver, 5% minimum dimming level, PF >0.90. protections include short circuit, input/output isolation and surge protection (3KV). wired for 0-10v dimming from factory.

mounting standard
driver in junction box (requires 2 1/8" deep electrical box). ultrathin vertical stainless steel cables and field adjustable grippers that allow for exact AFF mounting heights. cloth-covered power cord color options listed below. cloth cord requires special stripping tool (link). special universal mounting bracket allows EC to clock fixture orientation during installation. 5" sq. canopy painted to match fixture. satin black canopy and cord standard on wood finishes.

canopy mounted driver (CDVR) (optional)
5" sq. canopy with 3.5" x 3.5" extruded square, painted to match fixture (see image below). satin black canopy standard on wood finishes.

remote enclosure (LV) (optional)
the standard driver can be remote mounted up to 33ft from the LED. suspension length should be considered in distance. remote enclosure supplied. for distances greater than 33ft consult factory. for Chicago Plenum installation consult factory.

power over cable (POC) (optional)
Class 2 LED powered suspension system that suspends and powers the fixture with thin stainless steel copper-core conductive cables, providing a clean look without the need for a separate power cord. powered suspension requires cable cutter (link) specifically designed to cut stainless steel aircraft cable from 1/32" to 1/8". 5"sq canopy painted to match fixture. satin black canopy standard on wood finishes.

finish
select from 15 standard powder coat paint finishes or 3 wood finishes (listed below) or specify RAL# for custom colors. satin black canopy and cord standard on wood finishes.


emergency
if required, recommend use of inverter (by other).

catalog number



size	beam	CCT	lumens	painted finish	power cord	options
P6612 driver in j-box	S 20° spot	27 2700K	L1 410 lm		BUPC blue cloth cord	3FT 36" cable(s)
P6612.LV remote enclosure 3.5"dia X 12"ht	M 30° med	30 3000K	L2 715 lm	AP anodized paint	ORPC orange cloth cord	6FT 72" cable(s)
	W 50° wide	35 3500K	L3 1025 lm	BS brass	PLPC purple cloth cord	CDVR canopy mounted driver
	XW 90° extra wide	40 4000K	H1 1435 lm	BU blue	RDPC red cloth cord	
P6618 driver in j-box			H2 2050 lm	BZ bronze	WGPC white & gray dot cloth cord	
P6618.LV remote enclosure 3.5"dia X 18"ht			H3 2870 lm	CP champagne		
				FB flat black	POC power over cable	
P6624 driver in j-box				GM gun metal	WHPC white cord	
P6624.BABA driver in j-box				MB military blue	BKPC black cord	
P6624.LV remote enclosure 3.5"dia X 24"ht				MW matte white	SBPC silver braid cord	
				OR orange		
				RD red		
				SB satin black		
				SS satin silver		
				TG textured gray		
				YO yellow		


premium finish
RAL specify RAL#

wood finish
ASH ashwood
ENG english brown oak
ESP espresso
satin black canopy and cord standard on wood finishes



This product meets the guidelines for the Build America, Buy America Act. Some Exclusions Apply. For more information and full list of eligible SKUs, please contact the factory at info@impactltg.com




impactltg 


Calculation Table

The application of a Light Loss Factor is required to:


- match the lumen output for the power module specified
- incorporate the increased lumen output due to LED/Driver upgrades




20921
P7506-S-40H3
S 20° spot



20922
P7506-M-40H3
M 30° med



20923
P7506-W-40H3
W 50° wide




20924
P7506-EW-40H3
XW 90° extra wide

Cat No	Delivered* Lumens	Watts 120V / 277V	IES File #**	LLF to be applied
L1	410	4	W 20923	.13
L2	715	7	W 20923	.23
L3	1025	10	W 20923	.32
H1	1435	14	W 20923	.45
H2	2050	20	W 20923	.65
H3	2870	28	W 20923	.91
	S 20° spot	M 30° med	W 50° wide	XW 90° extra
ies file #	20921	20922	20923	20924

*delivered lumens based on 4000K, 90+ cri **choose the file that matches your beam spread

Typical Lighting Layout

Schedule						
Symbol	Quantity	Manufacturer	Catalog Number	Description	Lamp	Wattage
	1	Impact Architectural Lighting	P7512 W 40 H2	12" length sq.3 downlight cylinder	4000k 90cri LED	21



Plan View
Scale - 1" = 2ft

Statistics


Description	Symbol	Avg	Max	Min	Max/Min	Avg/Min
sq.3	+	26.9 fc	46.7 fc	14.9 fc	3.1:1	1.8:1

- 10' x 10' x 14'H space
- 80/50/20 reflectances
- bottom of fixture at 10' aff
- FC readings at 2.5' aff
- layout conducted using H2 lumen output 1985 lumens unit w/ 50-deg. beam spread

impactltg



Powder Coat Paint Finishes



MW matte white




AP anodized paint




SS satin silver



TG textured gray




FB flat black



SB satin black



CP champagne



BZ bronze



GM gun metal



OR orange 2011



BU blue 5017



BS brass



RD red 3020




YO yellow 1018




MB military blue

Premium Finishes*


Wood Finishes



ASH ashwood



ENG english brown oak



ESP espresso

For accurate color verification, actual finish samples are available upon request.



RAL#

*Available on select series. Consult product submittal for availability.

