

job name:

type:

36"/48" wāf.r.3™ spec sheet 90CRI

material
trim ring
wafer thin 3" h roll formed aluminum extrusion. 6061 T1 alloy. .100 typ. wall. available in 15 standard powder coat paint finishes listed below. premium RAL and wood finishes also available.

diffuser
satinice WD855 minimum 72% light transmission, light scattering, glare reduction, colorless diffusion acrylic.

optics
reflector
.080" aluminum array platform painted high reflectance (>92%) matte white powder coat provides 100% downlight. for uplight, specify under options.

LED
specification-grade LED modules with integrated batwing optics to minimize diffusion depth and increase illumination uniformity. 90+ CRI. L80>72,000 hrs. 3000K, 3500K, 4000K.

driver
integral, programmable, UL class P, class2, universal input (120-277v), constant current, 0-10v controllable, 1% minimum dimming level. complies with Energy Star®, DLC (DesignLights Consortium™), and CA Title 24 technical requirements.


mounting
5" dia. spun steel canopy in satin white is designed to mount to a 4" octagon junction box (by other). 6' tripod suspension of stainless steel cables attaches to reflector with field adjustable grippers that allow for exact AFF mounting heights. slip ring coupler at ceiling allows for easy wire connections. or select 12ft adjustable suspension. (drawing below)

finish
select from 15 standard powder coat paint finishes listed below. premium RAL and wood finishes also available.




emergency
recommend use of inverter (by other). optional WREM: wired for remote EM battery (by other).



catalog number

size	CCT	lumens	paint	power cord	options
P5636 (3ft) 36"dia X 3"ht	30 3000K 35 3500K 40 4000K	FX 4900 lm LO 7400 lm HI 9200 lm HX 13900 lm CL xxxx lm custom lumens consult factory 4900 - 13900 lm	AP anodized paint BS brass BU blue BZ bronze CP champagne FB flat black GM gun metal MB military blue MW matte white OR orange RD red SB satin black SS satin silver TG textured gray YO yellow	WHPC white power cord and canopy BKPC black power cord and canopy SBPC silver braid power cord and white canopy	6FT 72" adj cables 12FT 12ft adj suspension UP uplight WREM wired for remote EM battery pack (by other) (see note above) ELD EIdoLED* LUT Lutron* *consult factory
P5648 (4ft) 48"dia X 3"ht	30 3000K 35 3500K 40 4000K	FX 8100 lm LO 11600 lm HI 14800 lm HX 23000 lm CL xxxx lm custom lumens consult factory 2700 - 7000 lm	premium finish RAL specify RAL# wood finish ASH ashwood ENG english brown oak ESP espresso		
	RGBW35 TW2765	RGBW 3500K tunable white 2700K - 6500K			
	RGBW35 TW2765	RGBW 3500K tunable white 2700K - 6500K			





min. suspension length.


	X
P5618	5"
P5624	6.5"
P5636	9"
P5648	12.5"




Calculation Table

The application of a Light Loss Factor is required to:


- match the lumen output for the power module specified
- incorporate the increased lumen output due to LED/Driver upgrades




L062510501
P5618-40HI



L062510503
P5624-40HI



L062510504
P5636-40HI




L062510505
P5648-40HI

Cat No	Delivered* Lumens	Watts 120V / 277V	IES File #	LLF to be applied
P5618 FX	1350	15	L06251051	.43
P5618 LO	2350	30	L06251051	.74
P5618 HI	2700	36	L06251051	.85
P5624 FX	2700	27	L06251053	.43
P5624 LO	4100	43	L06251053	.65
P5624 HI	4900	52	L06251053	.77
P5624 HX	7000	79	L06251053	1.11
P5636 FX	4900	47	L06251054	.40
P5636 LO	7400	70	L06251054	.60
P5636 HI	9200	90	L06251054	.74
P5636 HX	13900	148	L06251054	1.12
P5648 FX	8100	72	L06251055	.39
P5648 LO	11600	107	L06251055	.56
P5648 HI	14800	142	L06251055	.72
P5648 HX	23000	231	L06251055	1.12

*delivered lumens based on 4000K, 90+ cri

Typical Lighting Layout

- 20' x 20' x 18'H space
- 80/50/20 reflectances
- bottom of fixture at 15' aff
- FC readings at 2.5' aff
- layout conducted using HI lumen package (9200 delivered lumens)




Schedule						
Symbol	Qty	Manufacturer	Test#	Description	LED	LLF
	1	Impact Architectural Lighting	L062510504 . P5636 40HI . WAF_R_3	P5636 40 HI	4000K 90CRI	0.740

Statistics					
Description	Avg	Max	Min	Max/Min	Avg/Min
waf.r.3 36" diameter	14.64 fc	24 fc	8 fc	3.00	1.83

Typical Lighting Layout

- 40' x 20' x 18'H space
- 80/50/20 reflectances
- bottom of fixture at 15' aff
- FC readings at 2.5' aff
- layout conducted using LO lumen package
24" - 4100 lm
36" - 7400 lm
48" - 11600 lm




Schedule						
Symbol	Qty	Manufacturer	Test#	Description	LED	LLF
	2	Impact Architectural Lighting	L062510504 . P5636 40HI . WAF_R_3	P5636 40LO	4000K 90CRI	.60
	3	Impact Architectural Lighting	L062510503 . P5624 40HI . WAF_R_3	P5624 40LO	4000K 90CRI	.65
	2	Impact Architectural Lighting	L062510505 . P5648 40HI . WAF_R_3	P5648 40LO	4000K 90CRI	.56

Statistics					
Description	Avg	Max	Min	Max/Min	Avg/Min
waf.r.3 24", 36", & 48" diameters	42.43 fc	54 fc	20 fc	2.70	2.12



Powder Coat Paint Finishes



MW matte white



AP anodized paint



SS satin silver



TG textured gray



FB flat black




SB satin black



CP champagne



BZ bronze



GM gun metal



OR orange 2011



BU blue 5017



BS brass



RD red 3020




YO yellow 1018




MB military blue

Premium Finishes*


Wood Finishes



ASH ashwood



ENG english brown oak



ESP espresso

For accurate color verification, actual finish samples are available upon request.



RAL#

*Available on select series. Consult product submittal for availability.

