

job name:
 type:

maxx™ spec sheet

material

trim ring
 precision CNC spun .063" aluminum. rolled bottom edge for added strength.

diffuser
 .187" virgin matte white acrylic dome held in place with allen key set screws recessed into trim ring.

top dome
 .125" colored acrylic, available in a variety of colors. subtle glow.

optics

reflector
 .050" aluminum array platform painted high reflectance (>92%) matte white powder coat. downlight reflector with minimal indirect light to illuminate top dome.

LED

custom LED board in 3000K, 3500K, or 4000K (80+ cri standard) optional 90cri (see below). under normal operating conditions, the LEDs employed are rated for >50,000hrs L70 (6.8K) per IES TM-21 from LM-80 test data. white power cord is standard with other color options listed below.

driver


integral, programmable, UL class P, class 2, universal input (120-277v), constant current, 0-10v dimming, 1% minimum dimming level, PF >.9, THD <20%, protections include open and short circuit, overload and over temperature.

mounting

5"dia. spun steel canopy in satin white with sloped ceiling adapter. single 12' stainless steel cable connects to field adjustable collector. An array of cables branch off and attach to trim with adjustable grippers. cable system allows for exact AFF mounting heights. sloped ceiling adapter.

emergency

recommend use of inverter (by other).







catalog number

--	--	--	--	--

size	top dome	LED array	painted finish	options
P7726 (2ft) 26"dia X 8.75"ht	B blue	30FX 3000K	AP anodized paint	90CRI
	O orange	30LO 3000K	BS brass	BKPC Black power cord and canopy
	R red	30HI 3000K	BU blue	SBPC Silver braid power cord and white canopy
P7738 (3ft) 38"dia X 11.75"ht	W white	35FX 3500K	BZ bronze	
		35LO 3500K	CP champagne	
		35HI 3500K	FB flat black	
		40FX 4000K	GM gun metal	
		40LO 4000K	MB military blue	
		40HI 4000K	MW matte white	
		CL xxxx lm custom lumens consult factory	OR orange	
			RD red	
			SB satin black	
			SS satin silver	
			TG textured gray	
			YO yellow	


premium finish
 RAL specify RAL#






Cat No	Delivered* Lumens	Watts		Amps	
		120V / 277V	120V	277V	
P7726 FX	2340	28	.23	.10	
P7726 LO	4680	57	.48	.21	
	ies file # 18696				
P7726 HI	7020	85	.71	.31	
	ies file # 18697				
P7738 FX	4180	50	.42	.18	
P7738 LO	8360	101	.84	.36	
P7738 HI	13370	162	1.35	.58	
	ies file # 18698				


*delivered lumens based on 4000K, 80+ cri
(90cri multiplier .83)




Powder Coat Paint Finishes



MW matte white




AP anodized paint




SS satin silver



TG textured gray




FB flat black



SB satin black



CP champagne



BZ bronze



GM gun metal



OR orange 2011



BU blue 5017



BS brass



RD red 3020



YO yellow 1018



MB military blue

For accurate color verification, actual finish samples are available upon request.

Premium Finishes*



RAL#

*Available on select series. Consult product submittal for availability.

